SL Series

Programmable DC Power Supply

CERTIFICATIONS



POWER	VOLTAGE	CURRENT	MODELS	SIZE
1.5 kW to 10 kW	5 Vdc to 1,500 Vdc	1.5 Adc to 250 Adc	127	1U

1 Description

The SL Series packs 1.5 to 10 kW of programmable DC power into an ultra-compact 1U rack-mount footprint, ideal for dense ATE and OEM racks. With 127 models spanning 5 to 1500 V and 1.5 to 250 A, the SL Series is designed to address a wide range of applications. High-efficiency thermal design and UL/CSA, CE Mark, and NRTL safety listings minimize cooling and certification overhead, streamlining system integration.

2 Key Features

- 127 models
- 1U rack-mount
- 1.5 kW, 2.6 kW, 4 kW, 6 kW, 8 kW, 10 kW power levels
- 5 Vdc to 1500 Vdc output voltage
- 1.5 Adc to 250 Adc output current
- UL/CSA listed, CE Mark
- Designed and manufactured in the USA

3 Integrated Options Available

+HS	High Slew Rate Output
+GPIB	IEEE-488 GPIB
+LXI	LXI TCP/IP Ethernet
+RUG	Ruggedized

4 Specifications

Specifications are subject to change without notice. Unless otherwise noted, all specifications measured at the product's maximum ratings.

4.1 AC Input Specifications

PARAMETER	VALUE	CONDITIONS
1Φ AC Input Voltage	100-240 Vac (UI: Universal input; 1.5 kW Models) 208-240 Vac (UI2: Universal input 2; 2.6 kW Models)	1Φ, 2-wire + ground
3Φ AC Input Voltage	208 Vac (operating range 187 to 229 Vac) 240 Vac (operating range 216 to 264 Vac) 380 Vac (operating range 342 to 440 Vac) 415 Vac (operating range 373 to 456 Vac) 440 Vac (operating range 396 to 484 Vac) 480 Vac (operating range 432 to 528 Vac)	3Φ, 3-wire + ground
Input Frequency	50 Hz to 400 Hz	
Power Factor	0.99 at maximum power for models with 1Φ AC input; Active-PFC > 0.82 at maximum power for models with 3Φ AC input	
AC Input Isolation	±2500 Vdc, maximum input voltage to ground	

4.2 DC Output Specifications

PARAMETER	VALUE	CONDITIONS
Voltage Ripple	Model specific. Refer to chart of available models.	
Line Regulation	Voltage mode: ± 0.004% of full scale Current mode: ± 0.02% of full scale	
Load Regulation	Voltage mode: ± 0.01% of full scale Current mode: ± 0.04% of full scale	
Stability	± 0.10% for 8 hrs. after 30 min. warm-up	
Efficiency	84% to 95% Model specific. Refer to chart of available models.	
Maximum Slew Rate	< 170 ms for a programmed output voltage change from 0 to 63% < 200 ms for a programmed output current change from 0 to 63%	Standard Models
Maximum Slew Rate	< 5 ms for a programmed output voltage change from 0 to 63% < 10 ms for a programmed output current change from 0 to 63%	Models with High Slew Rate Output (+HS) Option
Bandwidth	3 Hz with remote analog voltage programming 2 Hz with remote analog current programming	Standard Models
Bandwidth	60 Hz with remote analog voltage programming 45 Hz with remote analog current programming	Models with High Slew Rate Output (+HS) Option
DC Output Isolation	±1500 Vdc, maximum output voltage to ground	

4.3 Programming Interface Specifications

PARAMETER	VALUE	CONDITIONS
Front Panel Programming	Stepless aluminum rotary knobs and keypad	
Computer Interface	RS232, D-sub DB-9, female (Standard) LXI TCP/IP Ethernet RJ45 (Option +LXI) IEEE-488 GPIB (Option +GPIB)	

4.3 Programming Interface Specifications

PARAMETER	VALUE	CONDITIONS
External User I/O Port	37-pin D-sub DB-37, female Referenced to Earth ground; isolated from power supply output See User Manual for pin layout	Analog and Digital Programming
Remote Sense Limits (Wired)	3% maximum voltage drop from output to load	Available for models ≤ 1000 Vdc

4.4 Accuracy Specifications

PARAMETER	VALUE	CONDITIONS
Voltage Programming Accuracy	± 0.075% of max rated voltage	
Over Voltage Trip Programming Accuracy	± 0.075% of max rated voltage	
Current Programming Accuracy	± 0.075% of max rated current	
Over Current Trip Programming Accuracy	± 0.075% of max rated current	
Voltage Readback Accuracy	± 0.2% of max rated voltage	
Current Readback Accuracy	± 0.2% of max rated current	

4.5 External User I/O Specifications

PARAMETER	VALUE	CONDITIONS
Analog Programming and Monitoring Levels	0-10 Vdc	
Analog Output Impedances	Voltage output monitoring: 100 Ω Current output monitoring: 100 Ω +10V reference: 1 Ω	
Digital Programming and Monitoring Limits	Input: 0 to 5 Vdc, 10 kΩ input impedance Output: 0 to 5 Vdc, 5 mA drive capacity	

4.6 Physical Specifications

PARAMETER	VALUE	CONDITIONS
Racking Standard	EIA-310	
Rear Support Rails	Included	
Size and Weight	1U 1.75" H x 19" W x 24" D (4.4 x 48.3 x 61.0 cm) 32 lbs (14.52 kg)	1.5 kW Models
Size and Weight	1U 1.75" H x 19" W x 24" D (4.4 x 48.3 x 61.0 cm) 34 lbs (15.42 kg)	2.6 kW Models
Size and Weight	1U 1.75" H x 19" W x 24" D (4.4 x 48.3 x 61.0 cm) 35 lbs (15.88 kg)	4 kW Models
Size and Weight	1U 1.75" H x 19" W x 24" D (4.4 x 48.3 x 61.0 cm) 35 lbs (15.88 kg)	6 kW Models
Size and Weight	1U 1.75" H x 19" W x 24" D (4.4 x 48.3 x 61.0 cm) 36 lbs (16.33 kg)	8 kW Models
Size and Weight	1U 1.75" H x 19" W x 24" D (4.4 x 48.3 x 61.0 cm) 37 lbs (16.78 kg)	10 kW Models

4.7 Environmental Specifications

PARAMETER	VALUE	CONDITIONS
Ambient Operating Temperature	-25°C to 50°C	
Storage Temperature	-40°C to +85°C	
Humidity	Relative humidity up to 95% non-condensing	
Temperature Coefficient	0.04%/°C of maximum output voltage 0.06%/°C of maximum output current	
Air Flow	Side air inlet, rear exhaust	

4.8 Regulatory Specifications

PARAMETER	VALUE	CONDITIONS
EMC	Complies with 2014/30/EU (EMC Directive) CISPR 22 / EN 55022 Class A	
Safety	NRTL Listed, Nemko Certificate NA202512380 CSA C22.2 No. 61010-1:12; A1:2018 UL 61010-1:Ed.3,2012(R2019)	
CE Mark	Yes	
RoHS Compliant	Yes	

5 Model Ordering Guide

SL 800-10/208+HS+LXI

Product Series

Max Voltage

Max Current

Front Panel Type
(Empty): Standard
C: Blank
Note: Computer control and 37-pin isolated I/O included with all front panel types

Input Voltage
UI: 85 - 265 1Φ (1.5 kW Models)
UI2: 187 - 265 1Φ (2.6 kW Models)
208: 208 Vac 3Φ
240: 240 Vac 3Φ
380: 380/400 Vac 3Φ
415: 415 Vac 3Φ
440: 440 Vac 3Φ
480: 480 Vac 3Φ

Option Codes

6 Models

Max Voltage Vdc	1.5 kW	2.6 kW	4 kW	6 kW	8 kW	10 kW	Ripple mVrms	Efficiency
			Max Current Adc					
5	250	—	—	—	—	—	30	84%
10	150	250	—	—	—	—	30	89%
16	93	162	250	—	—	—	40	89%
20	75	130	200	250	—	—	40	90%
25	60	104	160	240	—	—	50	91%
32	46	81	125	186	250	—	60	91%
40	37	65	100	150	200	250	80	91%
50	30	52	80	120	160	200	70	92%
60	25	43	66	100	133	166	100	93%
80	18	32	50	75	100	125	120	93%
100	15	26	40	60	80	100	120	93%
125	12	20	32	48	64	80	110	93%
160	9	16	25	36	50	60	110	93%
200	7.5	13	20	30	40	50	110	94%
250	6	10.4	16	24	32	40	110	94%
300	5	8.6	13.2	20	26.4	33.3	120	94%
375	4	6.9	10.4	16	21.3	26.5	120	94%
400	3.7	6.5	10	15	20	25	170	95%
500	3	5.2	8	12	16	20	250	95%
600	2.5	4.3	6.4	10	13.3	16.5	250	95%
800	1.8	3.2	5	7.5	10	12.5	250	95%
1000	1.5	2.6	4	6	8	10	400	95%
1250	1.2	2	3.2	4.8	6.4	8	700	95%
1500	1	1.7	2.6	4	5.3	6.6	1000	95%
AC Input Voltage Vac			**Input Current Per Phase** Aac					
UI (85-265 Vac, 1Φ)	21 - 7	—	—	—	—	—		
UI2 (187-265 Vac, 1Φ)	—	16 - 12	—	—	—	—		
208/240 Vac, 3Φ	6	11	16	24	32	39		
380/415 Vac, 3Φ	5	8	11	16	19	22		
440/480 Vac, 3Φ	4	6	9	14	17	19		

7 Features

Fast, accurate power delivery with controls and options tailored to your needs

Unparalleled 1U power and performance

Clean, precise output with fast response for demanding systems.



SL Series supplies deliver fast transient response, high-accuracy programming and measurement, 12-bit resolution, and low output ripple—all in a class-leading 1U package with efficiency up to 95%. With constant-voltage or constant-current operation and automatic crossover, they settle quickly after load steps (load transient recovery on the order of a few milliseconds) and hold tight to your targets, with voltage and current programming accuracy up to ±0.075% of full scale—ideal for precision test, burn-in, and process applications where both dynamics and accuracy matter.

Configured-to-order with integrated options

Rich standard features, extended when needed.




SL Series starts with a strong base: SCPI over RS232, isolated 37-pin user I/O, LabVIEW and IVI drivers, and Remote Interface Software included. When applications demand more, fully integrated options tailor performance, connectivity, and mechanics—without external boxes or ad-hoc wiring.

- Standard SCPI computer controls, RS232, isolated 37-pin analog/digital I/O, LabVIEW & IVI drivers, RIS software.
- High Slew Rate Output (+HS) for higher bandwidth and faster programmed rise times.
- Connectivity options LXI TCP/IP Ethernet (+LXI) and IEEE-488 GPIB (+GPIB).
- Ruggedized (+RUG) for MIL-STD shock & vibration

Stepless front-panel control with blank panel option

Hands-on where you want it, hidden where you don't.




The standard SL front panel provides rotary and key-based control, bright digital metering, and clear status indicators, so operators can configure setpoints, start and stop the supply, and see system health at a glance. For OEMs and production tools, the optional blank (C-version) front panel removes local controls altogether while retaining full control via communication interfaces and rear 37-pin user I/O, keeping systems secure, clean, and operator-proof.

Rugged by design: safety + reliability, as you'd expect from Magna-Power.

Reliable current-fed power processing

Rugged by design: self-protecting topology for uptime.



MagnaDC power supplies utilize a high-frequency, current-fed architecture that adds a control stage beyond conventional voltage-fed designs. This topology inherently limits fault energy—avoiding fast-rising current spikes and magnetic core saturation so the supply self-protects and your load stays safe. Paired with state-of-the-art SiC power semiconductors, Magna DC power supplies delivers class-leading power density, efficiency, and reliability, including continuous full-power operation up to 50°C ambient.

- Current-fed architecture with an added control stage vs. voltage-fed.
- Inherent surge immunity—no current spikes or core saturation.
- Self-protecting behavior under fault conditions.
- SiC devices for high density and efficiency; full power to 50°C.

Safety features & interlock

Soft-start, programmable protection, and a mechanical line disconnect for true safety.



MagnaDC supplies start gently and watch continuously. A soft-start stage keeps inrush below steady-state draw, while built-in diagnostics monitor line, thermal, and control conditions. In standby or on a diagnostic fault, an embedded AC contactor mechanically disconnects the mains, assuring the unit only processes power when intended. Faults are shown on the front-panel status display, through 5V digital outputs, and are queryable via SCPI.

- Programmable trips: Over voltage (OVT) and over current (OCT).
- Control integrity: Program-line over-voltage detection.
- Over temperature product with multiple distributed thermal switches.
- Interlock/E-stop fault monitoring as a standard diagnostic.
- Field integration: 5V interlock input (with 5V reference) for a dry-contact, latching inhibit with control power maintained.

From lab scripts to factory PLCs, flexible programming & integration.

Software integration made easy


Readable commands, quick results—works with any language.

MagnaDC power supplies exposes a clear, text-based API with native SCPI, an ASCII-based command language sent over socket communications. Over 40 well-documented commands cover start/stop, set points for voltage, current, high-accuracy measurements, and full configuration—so your scripts and systems go from proof-of-concept to production fast.

- SCPI command sets with consistent behavior.
- Start/stop & protections: enable output, set trip limits, query status.
- High-accuracy reads: voltage, current, power, and sense feedback.
- Developer-driven documentation & examples.

External User I/O for PLC control or PHIL simulation

Wire it like an I/O module—no extra isolation needed.



Via the included rear 37-pin User I/O connector, MagnaDC supplies can be fully driven and monitored by external signals or a PLC. Voltage, current, OVT, and OCT set points are programmed with 0–10 V analog inputs, while each diagnostic condition has its own +5V digital status pin. Built-in +2.5V, +5V, and +10V reference rails let you use dry contacts without adding external supplies. All I/O is isolated from the output and referenced to earth ground as standard.

- 0–10 V analog programming for V, I, OVT, and OCT.
- Per-fault digital outputs: each diagnostic has its own +5V pin.
- Isolated user I/O referenced to earth ground—no extra isolators.
- With High Slew Rate Output (+HS), high-bandwidth response and fast rise times support HIL/PHIL simulation applications.

High-performance master-slave operation

Scale voltage or current without sacrificing performance.




All MagnaDC supplies support master-slave operation, using gate-drive signals from the master when configured for parallel, so the whole stack behaves like a single supply—with one control loop and no noisy long analog references. The optional UID47 accessory simplifies wiring for series or parallel sets with near-equal sharing.

- Single control loop parallel operation: Master gate-drive to slaves for consistent dynamics.
- Plug & play with the UID47, enabling parallel or series stacks with current/voltage sharing.
- Series up to the DC isolation rating without added hardware.
- No additional ORing diodes required for parallel operation.

Magna-Power software, LabVIEW & IVI drivers

From virtual front panel to full automation—out of the box.



Every MagnaDC supply includes an IVI driver and NI LabVIEW driver with a full set of VIs, plus example programs so you can get talking to the hardware in minutes. For direct front-panel-style control from a PC, Magna-Power's Remote Interface Software provides a rich view into the supply—from commands and registers to calibration and firmware.

- IVI & NI LabVIEW drivers included with full VI set.
- Example programs to jump-start integration and testing.
- Remote Interface Software with:
  - Virtual front panel for manual control
  - Command panel to explore and send commands
  - Register panel for live status monitoring
  - Calibration panel for internal digital potentiometers
  - Firmware panel for in-place upgrades
  - Modulation panel to emulate non-linear profiles
- All communication interfaces supported across software and drivers for a consistent programming experience.

State-of-the-art USA manufacturing with worldwide support

Made in the USA

Vertically integrated manufacturing for full quality control.




Magna-Power products are designed, built, tested, and serviced at Magna-Power's 73,500 sq-ft headquarters in Flemington, New Jersey, where metalwork, magnetics, PCB assembly, and burn-in are all done in-house for tight control over quality, cost, and lead-time.

- USA-built: Engineering, manufacturing, and service under one roof.
- In-house production: Metalwork, magnetics, SMT PCBs, and finishes.
- Proven reliability: Every unit fully tested, calibrated, and burned in.

Worldwide service & OEM parts support

Factory expertise, local response.




Magna-Power backs its products with factory and authorized service centers across North America, Europe, the UK, Asia-Pacific, East Asia, and South America—using factory procedures and genuine parts to restore units to original specifications, in or out of warranty.

- Global coverage: HQ in New Jersey plus regional authorized service centers.
- Consistent repairs: Factory diagnostics, work instructions, and system diagrams.
- Genuine OEM parts: Tested replacement assemblies for predictable, low-downtime service.


8 Diagrams

Front Panel




Top Panel


Rear Side



Rear Panel




Side Panel




Communications Interface

LXI TCP/IP Ethernet Option (+LXI)



Communications Interface

IEEE-488 GPIB Option (+GPIB)



9 Integrated Options Available

+HS High Slew Rate Output

A hardware and control modification that replaces the standard output stage with one of low capacitance film and/or high RMS current rated aluminum electrolytic capacitors. This option provides higher bandwidth with faster output rise and fall times.

The high slew rate option solves several limitations inherent in switching power supply design. Rapid voltage transitions require internal electronics to supply the energy to charge and discharge output capacitors. Peak currents internal to the power supply define slew rate; utilizing less capacitance enables voltage transitions in shorter time periods. Additionally, less capacitance reduces requirements for discharge demands during open circuit conditions.

The standard output stage Magna-Power Electronics power supplies has been designed to provide the lowest possible output ripple voltage within the constraints of available components, size, and cost. Part of the output stage consists of a bank of aluminum electrolytic capacitors which has the desired electrical properties to provide this function. These components require bleed resistors to discharge any voltage when the power supply has no load and is disabled. While the presence of these components and the resulting performance are normally industry accepted, there are applications where lower output capacitance and lower loss bleed resistors are extremely desirable and higher ripple voltage is acceptable. To meet this need, a high-slew rate option is available which has an output stage consisting of low capacitance film and aluminum electrolytic capacitors and lower loss bleed resistors. Applications for the high-slew rate option include battery charging, photovoltaic emulation, power waveform generation, and medium speed power pulsing. These applications all benefit from higher bandwidth and in many cases, can tolerate increased ripple voltage.

Key Applications

For **battery charger applications**, output capacitance and internal bleed resistors present themselves as a load to the connecting batteries. One common practice is to use a series diode to block reverse current flow with the sacrifice of increased cost and lower efficiency. The high slew rate option, with its lower output capacitance and lower loss bleed resistors, enables direct connection to batteries without series blocking diodes.

For **photovoltaic emulation applications**, higher bandwidth and lower output capacitance enable improved performance with higher speed, maximum power tracker algorithms. Maximum power tracker circuitry deviates the operating point of photovoltaic arrays to determine maximum power output. Slow responding emulation sources can present a problem when the speed of the algorithm exceeds that of the source. Furthermore, with lower output capacitance, changes in the operating point and transients, caused by shorting the solar inverter input, produce lower unwanted input currents.

The high-slew rate option enables the power supply to operate as a **low frequency, power pulse generator**. With the special capacitors selected for this option, it is possible to superimpose waveforms or produce a medium speed pulse on top of the dc output and expect normal capacitor life. It is important to note that the power supply output is single quadrant; that is, the output voltage or current cannot reverse.

Specifications

SL Series Output Stage Ratings with the High Slew Rate Output Option Integrated

Voltage Maximum Rating (Vdc)	Output Capacitance (uF)	Output Voltage Ripple (Vrms)
5	4235	0.5
10	1740	0.6
16	1740	0.6
20	775	0.6
25	775	0.8
32	775	0.8
40	760	1.5
50	760	1.5
60	760	2.0
80	110	1.5
100	110	1.6
125	70	1.7
160	70	1.8
200	70	1.8
250	70	1.8
300	70	1.8
375	70	1.8
400	70	1.8
500	40	2.0
600	40	2.2
800	30	2.5
1000	30	3.4
1250	—	3.4
1500	—	4.0

XR Series Output Stage Ratings with the High Slew Rate Output Option Integrated

Voltage Maximum Rating (Vdc)	Output Capacitance (uF)	Output Voltage Ripple (Vrms)
5	13200	1.5
10	4080	1.6
16	4080	1.7
20	2340	1.8
25	1170	1.8
32	1170	1.8
40	240	1.8
50	240	1.8
60	240	2.0
80	240	2.2
100	160	2.5
125	160	3.0
160	160	2.8
200	160	4.0
250	160	1.6
300	160	1.8
375	160	1.8
400	160	1.8
500	56	3.0
600	56	3.0
800	52	3.0

Voltage Maximum Rating (Vdc)	Output Capacitance (uF)	Output Voltage Ripple (Vrms)
1000	52	3.0
1250	18	3.5
1500	18	3.5
2000	18	5.0
3000-10000	—	—

TS Series Output Stage Ratings with the High Slew Rate Output Option Integrated

Voltage Maximum Rating (Vdc)	Output Capacitance (uF)	Output Voltage Ripple (Vrms)
5	13200	0.5
8	9000	0.5
10	9000	0.5
16	4080	0.5
20	2340	0.8
25	2340	0.8
32	1170	0.8
40	1170	0.8
50	1170	0.8
60	300	1.2
80	300	1.2
100	200	1.6
125	200	1.6
160	200	1.6
200	200	2.0
250	200	2.0
300	200	2.2
375	200	2.2
400	200	2.4
500	200	2.7
600	120	2.6
800	70	2.6
1000	60	3.5
1250	18	3.5
1500	18	4.3
2000	18	3.8
3000	9	7.2
4000	9	4.0

Note:
For 20 to 30 kW models, multiply capacitance by 2
For 40, 50, 75, and 100 kW models, contact Magna-Power support

For MT Series and ML Series output stage ratings with the high slew rate output option, please inquire with your local sales partner regarding the specific model.

+GPIB IEEE-488 GPIB

IEEE-488 General Purpose Interface Bus (GPIB) communication interface providing full command support and compatibility with other GPIB devices

The IEEE-488 interface, sometimes called the General Purpose Interface Bus (GPIB), is a general purpose digital interface system that can be used to transfer data between two or more devices. It is particularly well-suited for interconnecting computers and instruments. Some of its key features are:

- Up to 15 devices may be connected to one bus
- Total bus length may be up to 20 m and the distance between devices may be up to 2 m
- Communication is digital and messages are sent one byte (8 bits) at a time
- Message transactions are hardware handshaked
- Data rates may be up to 1 Mbyte/sec

The IEEE-488 GPIB interface in integrated with the power supply's rear communication ports. The IEEE 488 interface offers full compatibility with Magna-Power provided drivers, software and SCPI command set.

+LXI LXI TCP/IP Ethernet

TCP/IP Ethernet communication protocol and single RJ-45 interface, certified to the LXI Class C standard, for socket communications using conventional computer networks

Certified to the LXI Standard (Class C), version 1.4, this option allows the product to be fully controlled over an integrated TCP/IP Ethernet interface. LXI is an instrumentation platform based on industry standard Ethernet technology designed to provide modularity, flexibility, and performance to small- and medium-sized systems. All of the product's standard SCPI commands are supported over the +LXI option, along with all provided software and drivers.

LXI's advantages are exemplified in its compact, flexible package providing high-speed I/O and reliable measurements. The Magna-Power Electronics LXI TCP/IP Ethernet option includes an embedded web-server, allowing web browser power supply control and monitoring from virtually anywhere.

Note: For xGen products, only the SCPI command protocol is available when LXI TCP/IP Ethernet interface is installed. Modbus communication protocol is not available through any interface when the LXI TCP/IP Ethernet interface is installed.

+RUG Ruggedized

Internal product ruggedization, which has been independently tested to comply with select MIL-STD-810G and RTCA DO-160 shock and vibration specifications.

The Ruggedized Option (+RUG) provides additional mechanical security for large power components and sub-assemblies within SLx Series, SL Series, and XR Series products.

SLx Series, SL Series, and XR Series units with the Ruggedized Option have been independently tested to comply with the following MIL-STD-810G shock and vibration specifications:

- MIL-STD-810G CHG1 Method 516.7 Functional Shock, Procedure I; which subjects the product to 40G, 11 ms terminal saw tooth pulse; three shocks in each direction along three mutually perpendicular axes
- MIL-STD-810G CHG1 Method 514.7 Vibration; which subjects the product to two hours of vibration per axis along three mutually perpendicular axes

In addition to the specifications listed above, the air cooled SLx Series products with the Ruggedized Option have also been independently tested to comply with RTCA/DO-160G Section 8.0 Vibration, Profile B4 with its associated total energy of 2.2 G_{rms} for equipment installed in Fixed Wing aircrafts with Turbojet or Turbofan engines.

With the Ruggedized Option, SL Series and XR Series products maintain ambient operating temperatures from -25°C to 50°C, while SLx Series products maintain ambient operating temperatures from 0ºC to 50ºC. Storage temperature for all products is rated from -40°C to +85°C.

10 Product Images









Qty (30) 2.6 kW SL Series units packaged into Qty (2) CAB2, with enclosure panels removed [Angled]



SL Series power supply with the C Version front panel.



Qty (39) 6 kW SL Series units packaged into Qty (2) CAB2 [Left] and Qty (1) CAB1 [Right]



Qty (30) 2.6 kW SL Series units packaged into Qty (2) CAB2, with enclosure panels removed [Front]



Qty (30) 2.6 kW SL Series units packaged into Qty (2) CAB2, with enclosure panels removed [Rear]

11 Downloads

https://magna-power.com/products/magnadc/sl#downloads

12 Contact

Magna-Power Electronics, Inc.
39 Royal Road, Flemington, NJ 08822, United States of America
PHONE +1 908-237-2200 EMAIL sales@magna-power.com